



| Technical data      |                | S36             |                 |                 |
|---------------------|----------------|-----------------|-----------------|-----------------|
| Item No.            |                | 5101428         | 5101426         | 5101436         |
| Voltage             | V              | 230             | 230             | 120             |
| Power               | W              | 2300            | 3300            | 2200            |
| Frequency           | Hz             | 50/60           | 50/60           | 50/60           |
| Max. temperature    | °C             | 650             | 650             | 650             |
| Min. air flow       | l/min          | 240             | 370             | 240             |
| Air connection      | ∅ mm           | 19,0            | 19,0            | 19,0            |
| Air outlet          | ∅ mm           | 22,0            | 22,0            | 22,0            |
| Dimensions          | mm (l x w x h) | 225 x 69,5 x 58 | 225 x 69,5 x 58 | 225 x 69,5 x 58 |
| Weight              | kg             | 0,5             | 0,5             | 0,5             |
| Protection class II | □              |                 |                 |                 |
| Marking             | CE             |                 |                 |                 |

**Accessories**

| Item No. | Description                      |
|----------|----------------------------------|
| 5107250  | Flange connection                |
| 5107003  | Angle nozzle 90 degrees, ∅ 12 mm |
| 5107261  | Wide slot nozzle 70x4 mm         |
| 5107251  | Extension tube 210x36,5 mm       |

Different voltages, power and special versions, such as external activation via controller or SPS possible.

**Available on request!**

Special accessories on request!

